

UL 인증서

UL 94V test : V-0

Component - Plastics

E513180

Guide Information

Plastech Co Ltd

122-66, Sangdong-ro, Sangdong-myeon, Gimhae-si Gyeongsangnam-do 50805 KR

TG-100V0

Polycarbonate (PC) "Caborex", furnished as sheets or roll

<u>Color</u>	<u>Min. Thk</u> <u>(mm)</u>	<u>Flame</u> <u>Class</u>	<u>HWI</u>	<u>HAI</u>	<u>RTI</u> <u>Elec</u>	<u>RTI</u> <u>Imp</u>	<u>RTI</u> <u>Str</u>
NC	3.0	V-0	-	-	80	80	80
	5.0	V-0	-	-	80	80	80

Comparative Tracking Index (CTI): -

Inclined Plane Tracking (IPT) kV: -

Dielectric Strength (kV/mm): -

Volume Resistivity (10^x ohm-cm): -

High-Voltage Arc Tracking Rate (HVTR): -

Surface Resistivity (10^x ohms/square): -

Dimensional Change (%): -

High Volt, Low Current Arc Resis (D495): -

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2020-03-30

Last Revised: 2020-03-30

© 2022 UL LLC

